

# ZPMV8.E76251 - WIRING, PRINTED CERTIFIED FOR CANADA - COMPONENT

## Wiring, Printed Certified for Canada - Component

See General Information for Wiring, Printed Certified for Canada - Component

**WUERTH ELEKTRONIK GMBH & CO KG**  
 SALZSTR 21  
 74676 NIEDERNHALL, GERMANY

E76251


Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Solder Limits C sec	Max	Flame Class	Meets UL796 DSR	C T I	
	Min mm(in)	Min Edge mm(in)			Area Diam mm(in)		Oper Temp C				
<b>Multi layer printed wiring boards.</b>											
50	0.076 (0.003)	0.229 (0.009)	4.5 (0.18) Int:99	DS	127 (5.0)	288	20	130	V-0	All	3
52	0.076 (0.003)	0.229 (0.009)	5 (0.20) Int:35	DS	25.4 (1.0)	288	20	130	V-0	All	*
52A	0.076 (0.003)	0.229 (0.009)	5 (0.20) Int:35	DS	25.4 (1.0)	288	20	130	V-1	All	*
53 (c)	0.076 (0.003)	0.228 (0.009)	5 (0.20) Int:99	DS	25.4 (1.0)	288	20	130	V-1	All	*
53B (c)	0.076 (0.003)	0.228 (0.009)	5 (0.20) Int:99	DS	12.7 (0.5)	288	20	130	V-0	All	*
54	0.076 (0.003)	0.229 (0.009)	4.5 (0.18) Int:99	DS	127 (5.0)	288	20	130	V-0	All	*
59	0.05 (0.002)	0.05 (0.002)	5 (0.20) Int:70	DS	50.8 (2.0)	288	20	130	V-0	All	3
<b>Multilayer Flexible Materials Interconnect connections (FMIC) with Flammability Classification only.</b>											
56	-	-	-	DS	-	288	20	-	V-0	-	-
65	-	-	-	DS	-	288	17	-	V-0	-	-
65A	-	-	-	DS	-	288	17	-	V-1	-	-
<b>Multilayer metal based printed wiring boards, flammability only Recognition.</b>											
58	-	-	-	SS	-	288	20	-	V-0	-	-
<b>Multilayer printed wiring boards.</b>											
912	0.08 (0.003)	0.15 (0.006)	17 (0.67) Int:175	DS	76 (3.0)	288	20	130	V-0	All	*
<b>Multilayer printed wiring boards, flammability only Recognition.</b>											
51	-	-	-	DS	-	288	20	-	V-0	-	-
83	-	-	-	DS	-	288	20	-	V-0	-	-
<b>Multilayer Rigid/Flex-to-Install Printed Wiring Boards.</b>											
66 @	0.075 (0.003)	0.20 (0.008)	18 (0.71) Int:70	DS	25.4 (1.0)	288	20	120	V-1	All	4
67 @	0.075 (0.003)	0.20 (0.008)	35 (1.38) Int:35	DS	25.4 (1.0)	288	20	120	V-0	All	3
68 @	0.075 (0.003)	0.20 (0.008)	35 (1.38) Int:35	DS	25.4 (1.0)	288	20	120	V-1	All	2
<b>Single layer printed wiring boards.</b>											
11	0.076 (0.003)	0.229 (0.009)	16.5 (0.65)	DS	127 (5.0)	288	20	130	V-0	All	3
12	0.076 (0.003)	0.229 (0.009)	5 (0.20)	DS	25.4 (1.0)	288	20	130	V-0	All	*
12A	0.076 (0.003)	0.229 (0.009)	5 (0.20)	DS	25.4 (1.0)	288	20	130	V-1	All	*
14	0.076 (0.003)	0.229 (0.009)	16.5 (0.65)	DS	127 (5.0)	288	20	130	V-0	All	*
911	0.08 (0.003)	0.15 (0.006)	17 (0.67)	DS	50.8 (2.0)	288	20	130	V-0	All	*
<b>Single layer printed wiring boards, flammability only Recognition.</b>											
13	-	-	-	DS	-	288	20	-	V-0	-	-

(c) - Board employs embedded, uninsulated wires welded to copper foil

@ - Minimum external Cu thickness in the rigid portion is 12 mic. Maximum internal Cu thickness in rigid portion is 70 mic. Minimum external and maximum internal Cu values indicated refers to flexible portion of the board.

NOTE - Type designations may be followed by 0.

\* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or tradename "WE" , or file number and type designation and the Recognized Component Mark for Canada,  . May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2019-03-15

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

This document is (c) 2019 UL LLC

Reprinted from the Online Certifications Directory with permission from UL